



NFPA Recommended  
Standard NFPA/T3.10.5.1  
R2-2000 (R2019)

Third edition  
15 March 2000

---

AN INDUSTRY STANDARD FOR FLUID POWER

**Hydraulic filter/separator housing – Pressure rating supplement to  
NFPA/T2.6.1 R2-2000, Fluid power components – Method for  
verifying the fatigue and establishing the burst pressure ratings of  
the pressure containing envelope of a metal fluid power  
hydraulic filter/separator**

**(Revision of NFPA/T3.10.5.1 R1-1997, R2-2000)  
Reaffirmed 2019**

**Descriptors:** hydraulic filter separator housing fluid power RFP verification test constant amplitude pressure ratings pressure containing envelope copper based alloys statistical methods verification fatigue distribution data.

---

published by

**NATIONAL FLUID POWER ASSOCIATION, INC.**

6737 W. Washington St., Suite 2350 / Milwaukee, WI 53214 USA  
PHONE: +1 414 778 3344 / FAX: +1 414 778 3361 / E-mail: [nfpa@nfpa.com](mailto:nfpa@nfpa.com)

Copyright 2000 by the  
**NATIONAL FLUID POWER ASSOCIATION**  
Printed in the USA

All standards, recommended practices, information reports, and bibliographies (collectively, "NFPA Documents") are advisory only. Use thereof by anyone for any purpose is entirely voluntary and in any event without risk of any nature to the National Fluid Power Association (NFPA), its officers, directors or authors of such work. There is no agreement by or between anyone to adhere to any NFPA Document. In formulating and approving NFPA Documents, NFPA and/or its councils and committees will not investigate or consider citations, references or patents which may or may not apply to such subject matter since prospective users of such NFPA Documents alone are responsible for establishing necessary safeguards in connection with utilization of such matters, including technical data, proprietary rights or patentable materials.

The information and data contained in NFPA Documents has been obtained from sources believed to be reliable. However, it should not be assumed that all acceptable or applicable sources of information, procedures, methods or techniques are contained in NFPA Documents, or that additional measures may not be required under certain circumstances or conditions.

NFPA Documents and/or policies and procedures are subject to periodic review and may be changed without notice. NFPA Documents are only current as of their publication date. NFPA Documents, after publication, may be revised or withdrawn at any time and current information on all NFPA Documents may be received by calling or writing NFPA. Additionally, the various codes and regulations referenced in NFPA Documents may be amended from time to time and it should not be assumed that the versions referenced therein are the most current versions of such codes and regulations. Please consult the appropriate regulatory authorities for the most up-to-date versions.

NFPA Documents imply a consensus of those substantially concerned with their scope and provisions and are intended as a guide to aid the manufacturer, the consumer and the general public. The publication of NFPA Documents does not in any respect preclude anyone, whether they have participated in the development of or approved such NFPA Documents or not, from manufacturing, marketing, purchasing, or using of products, processes or procedures not conforming to the NFPA Documents. NFPA Documents do not constitute or indicate a warranty of any sort, express or implied, including but not limited to a warranty or representation as to quality, merchantability or fitness for a particular use or purpose.

Participation by federal agency representative(s) or person(s) affiliated with the industry is not to be interpreted as government or industry endorsement of an NFPA Document(s).

#### **NOTICE**

NFPA Documents do not express or imply any judgment, certification or endorsement of or with respect to, the safety, design or performance of any product, component, or its use.

NFPA does not examine, investigate, test, recommend, or certify the design, use or safety of any product or component, even those which may incorporate one or more NFPA Documents. NFPA Documents therefore have no application to and do not express or imply any recommendation, representation or warranty, with respect to the safety, design, use, performance, or functional interchangeability of components or products which incorporate NFPA Documents.

This publication may not, in whole or in part, be reproduced, copied or disseminated, entered into or stored in a computer database or retrieval system, or otherwise utilized without the prior written permission of NFPA.

## Foreword

This Foreword is not part of NFPA Recommended Standard *Pump/Motor – Pressure Rating Supplement to NFPA/T2.6.1 R2-2000, Fluid power components – Method for verifying the fatigue and establishing the burst pressure ratings of the pressure containing envelope of a metal fluid power pump and motor*, NFPA/T3.10.5.1 R2-2000

The project was initiated on 11 February 1997 and the TSP was approved by the Technical Board on 10 April 1997. The first draft was updated to coordinate the document with the updated NFPA/T2.6.1 R2. Both were issued for general review on 30 December 1998. Comments were reviewed at the T2.6 committee meeting of 9 February 1999, and proposed changes were reviewed by the T3.21 committee at its meeting of 18 May 1999. The ballot draft was prepared by NFPA headquarters on 2 August 1999. One negative ballot was reviewed at the T2.6 meeting on 22 September 1999. It was resolved and the Technical Board gave final approval on 18 November 1999.

Project group members who developed this standard:

**John Berninger**

Project Chairman and T2.6 Chairman  
Parker Hannifin Corp

**Paul Schacht**

Technical Auditor  
Bosch Automation Technology

**Kendall McBroom**

Section Chairman  
Nelson Industries, Inc.

**June VanPinsker**

Technical Coordinator  
National Fluid Power Association

**Kenneth Happach**

Section Vice Chairman  
Caterpillar Inc.

**Shirley C. Seal**

Manager of Standards Development –  
Industry/National  
National Fluid Power Association

**Bruce Shane**

Section Secretary  
Parker Hannifin Corp.

/jmv

## Introduction

In fluid power systems, power is transmitted and controlled through a fluid (liquid or gas) under pressure within an enclosed circuit. During operation, hydraulic filter/separator housing(s) in a system may be loaded from internal pressure, gravity, inertia, thermal variations and external forces. The nature of these loads can vary from a single static application, to continuously varying amplitudes, repetitive loadings and even shock.

It is important to know how well a hydraulic filter/separator housing(s) can withstand these loads, but, this standard addresses only the loading due to internal pressure.

There are many ways in which internal pressure loads are imposed upon a hydraulic filter/separator housing(s). This standard considers a broad range of waveforms but within prescribed time limits, temperatures, environmental conditions and only upon certain metals. It is anticipated that these limitations could still provide sufficient common ground for comparing products. This rating method, therefore, provides the system designer with certain information to assist in a selection of hydraulic filter/separator housing(s) for an application. The designer still has the responsibility to consider the other loading characteristics described above and to determine how they might affect the hydraulic filter/separator housing(s) ultimate pressure retaining capability.

There are many standards already in existence for pressure rating individual components (e.g. maximum allowable operating pressure) and this standard is not intended to displace them. Instead, a method of fatigue verification is provided.

This standard serves as a universal "verification test" to give credibility to the many in-house and other methods of determining hydraulic filter/separator housing(s) pressure ratings. The credibility is based upon the fundamental nature of fatigue of metals with its statistical treatment and use of the pressure rating verification theory developed in NFPA/T2.6.1 R2. Nevertheless, design knowledge of the hydraulic filter/separator housing(s) population and its representative samples, including consistency in materials, shapes, fabrication techniques, etc. is necessary to maximize accuracy in the verification method.

This standard describes specific methods for testing hydraulic filter/separator housing(s) verifying their fatigue pressure ratings and establishing burst pressure ratings. It also provides specific means to determine some of the optional parameters.

This standard is a supplement to the basic pressure rating standard, NFPA/T2.6.1 R2. It follows the provisions of that document but is more specific to hydraulic filter/separator housing(s). Application of this pressure rating method will require use of both documents.

This version of NFPA/T3.10.5.1 R2 replaces earlier editions and utilizes the same basic theory. Products rated under the first (1976) edition may not be rated to the same values under this edition. See clause 15 for the differences in rating identification.

# Hydraulic filter/separator housing – Pressure rating supplement to NFPA/T2.6.1 R2-2000, Fluid power components – Method for verifying the fatigue and establishing the burst pressure ratings of the pressure containing envelope of a metal fluid power hydraulic filter/separator

## 1 Scope

1.1 This standard provides:

- test and statistical methods for generating fatigue distribution data;
- test and statistical methods for conducting a verification of the pressure ratings on fluid power hydraulic filter /separator housing(s);
- common requirements and an industry-wide philosophy in judging one type of pressure capability for fluid power hydraulic filter/separator housing(s);
- uniform methods of product comparison.

1.2 This standard limits conditions as follows:

- constant amplitude, pressure induced loading of the elements that constitute or maintain the pressure containing envelope;
- product life of at least 100,000 cycles;
- defined conditions for pressure levels and pulse durations;
- temperatures from the charpy impact transition temperature to the threshold of creep sensitivity;
- environments which are chemically compatible with the materials of the pressure containing envelope;
- materials that are aluminum, magnesium, steel, iron, copper based alloys, cobalt, titanium, stainless steels, nickel steels and monel;
- specifically excluded are creep sensitive materials such as: zinc, plastic, rubber and sealing devices;
- to exclude the finite life RFP rating for a hydraulic filter /separator housing (such as spin-on filters) used in finite life applications. See NFPA/T3.10.17.

1.3 This standard encourages manufacturers to use this common method to enhance the credibility of their pressure ratings.