

NSF/ANSI 4 – 2005e

Commercial cooking, rethermalization, and powered hot food holding and transport equipment

NSF International Standard/
American National Standard

NSF/ANSI 4 – 2005e



NSF International, an independent, not-for-profit, non-governmental organization, is dedicated to being the leading global provider of public health and safety-based risk management solutions while serving the interests of all stakeholders.

*This Standard is subject to revision.
Contact NSF to confirm this revision is current.*

Users of this Standard may request clarifications and interpretations, or propose revisions by contacting:

Chair, Joint Committee on Food Equipment
c/o NSF International
789 North Dixboro Road, P.O. Box 130140
Ann Arbor, Michigan 48113-0140 USA
Phone: (734) 769-8010 Telex: 753215 NSF INTL
FAX: (734) 769-0109
E-mail: info@nsf.org
Web: <http://www.nsf.org>

NSF International Standard/
American National Standard
for Food Equipment —

**Commercial cooking, rethermalization,
and powered hot food holding
and transport equipment**

Standard Developer

NSF International

Adopted October 4, 2005

NSF International

Designated as a ANSI Standard

Approved October 4, 2005

American National Standards Institute

Prepared by
The NSF Joint Committee on Food Equipment

Recommended for adoption by
The NSF Council of Public Health Consultants

Adopted by
The NSF Board of Directors
August 1958

Revised July 1967
Revised August 1968
Revised April 1970
Revised July 1971
Revised April 1973
Revised June 1986
Revised May 1992

Revised May 1996
Revised March 1997
Revised May 1999
Revised November 2000
Revised March 2002
Revised October 2005
Editorial revision November 2005

Published by

NSF International
PO Box 130140, Ann Arbor, Michigan 48113-0140, USA

For ordering copies or for making inquiries with regard to this Standard, please reference the designation "NSF/ANSI 4 – 2005e."

Copyright 2005 NSF International

Previous Editions, © NSF 2002, 2000, 1999, 1997, 1996, 1992, 1986, 1973, 1971, 1970, 1968, 1967, and 1958

Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from NSF International.

Printed in the United States of America.

Disclaimers¹

NSF, in performing its functions in accordance with its objectives, does not assume or undertake to discharge any responsibility of the manufacturer or any other party. The opinions and findings of NSF represent its professional judgment. NSF shall not be responsible to anyone for the use of or reliance upon this Standard by anyone. NSF shall not incur any obligation or liability for damages, including consequential damages, arising out of or in connection with the use, interpretation of, or reliance upon this Standard.

NSF Standards provide basic criteria to promote sanitation and protection of the public health. Provisions for mechanical and electrical safety have not been included in this Standard because governmental agencies or other national standards-setting organizations provide safety requirements.

Participation in NSF Standards development activities by regulatory agency representatives (federal, local, state) shall not constitute their agency's endorsement of NSF or any of its Standards.

Preference is given to the use of performance criteria measurable by examination or testing in NSF Standards development when such performance criteria may reasonably be used in lieu of design, materials, or construction criteria.

The illustrations, if provided, are intended to assist in understanding their adjacent standard requirements. However, the illustrations may not include **all** requirements for a specific product or unit, nor do they show the only method of fabricating such arrangements. Such partial drawings shall not be used to justify improper or incomplete design and construction.

Unless otherwise referenced, the "normative" annexes are not considered an integral part of NSF Standards. The annexes are provided as general guidelines to the manufacturer, regulatory agency, user, or certifying organization.

¹ The information contained in this Disclaimer is not part of this American National Standard (ANS) and has not been processed in accordance with ANSI's requirements for an ANS. As such, this Disclaimer may contain material that has not been subjected to public review or a consensus process. In addition, it does not contain requirements necessary for conformance to the Standard.

Center for Public Health Education Training Courses



NSF/ANSI Standards Training Programs

A full schedule of classes developed to help manufacturers through the NSF/ANSI Certification process is offered at NSF Headquarters, at regional training sites, or at a location of your choice. Customized classes can be scheduled.



HACCP Manager Certification and Certified Professional Food Manager Classes and Publications

Classes in HACCP Management, Food Safety, Plan Review for Regulators, Optimizing the Cook & Thurber Audit, and Product Security are available throughout the year. NSF HealthGuard Training Series includes books on Food Manager Certification, HACCP Manager Certification, the Foodboss HACCP System Manual with CD, and conference proceedings.

The current training schedule and the educational materials are available at www.nsf.org/cphe.
For on-site custom training classes, please call 1-800-673-6275, ext. 5782.

Contents

Foreword	ix
1 General	1
1.1 Purpose	1
1.2 Scope	1
1.3 Alternative materials, design, and construction	1
1.4 Measurement	1
2 Normative references	2
3 Definitions	3
4 Materials	3
4.1 Conformance with NSF/ANSI 51	3
4.2 Solder	4
4.3 Gaskets	4
4.4 Fryer and steam cooker baskets	4
4.5 Fat/oil fryers and filters	4
4.6 Beverage equipment	4
5 Design and construction	5
5.1 General sanitation	5
5.2 Internal angles and corners	5
5.3 External angles and corners	6
5.4 Joints and seams	6
5.5 Fasteners	6
5.6 Insulation	7
5.7 Reinforcing and framing	7
5.8 Inspection and maintenance panels	7
5.9 Doors	8
5.10 Door tracks and guides	8
5.11 Door closers, handles, knobs, and pulls	8
5.12 Hinges	8
5.13 Covers	9
5.14 Edges and nosings	9
5.15 Openings to food zones	10
5.16 Louvers	10
5.17 Hardware	10
5.18 Handles and pulls	10
5.19 Latches and catches	10
5.20 Breaker strips	10
5.21 Equipment mounting	10
5.22 Legs and feet	11
5.23 Casters, rollers, and gliders	11
5.24 Shelving	11
5.25 Pipe chases	12
5.26 Enclosed spaces	12
5.27 Drawers	12
5.28 Insets	12
5.29 Food shields	12
5.30 Breakable glass components	12
5.31 Light fixtures	13
5.32 Plumbing connections	13
5.33 Entry ports	14

5.34	Cappuccino machines with milk reservoirs	14
5.35	Coffee urns.....	14
5.36	Jacketed kettles and urns	14
5.37	Steam tables and bains-marie	14
5.38	Popcorn cabinets	15
5.39	Hot food holding and hot food transport equipment.....	15
5.40	Proofing boxes and proofing cabinets.....	15
5.41	Rethermalization equipment	15
5.42	Equipment provided with a security package	15
6	Performance.....	16
6.1	Enclosed hot food holding equipment and hot food transport cabinets.....	16
6.2	Open top hot food holding equipment.....	17
6.3	Rethermalization equipment	18
6.4	Cleaning and sanitization procedures.....	19
6.5	Pyrolytic self-cleaning ovens.....	20
6.6	Abrasion resistance of asbestos cement flat sheet	21
6.7	Open Heated Merchandisers	21
7	Food equipment provided with a security package.....	22
7.1	General	22
7.2	Special tools.....	22
7.3	Fastening methods (splash zone).....	22
7.4	Fastening methods (nonfood zone).....	22
7.5	Hinges	23
7.6	Hardware.....	23
7.7	Shelf brackets, pilasters, slides, or cleats	23
7.8	Kick plate.....	23
7.9	Drawers	23
7.10	Conveyor units	23
7.11	Labeling.....	23
Figures		
	Figure 1 – External corners or angles.....	24
	Figure 2 – Single panel door.....	24
	Figure 3 – Openings and rims – food zone.....	25
	Figure 4 – Perforated false bottom	25
	Figure 5 – Diverting shelves	26
	Figure 6 – Interior fixed shelves.....	26
	Figure 7 – Rack slides.....	27
	Figure 8 – Pipe chases	27
	Figure 9 – Drawers.....	27
	Figure 10 – Test sample container pattern for open heated merchandisers	28
A	Procedures for the preparation of test media	A1
A.1	Test media for open hot food holding equipment	A1
A.2	Test media for rethermalization equipment	A2
B	Method for conducting in-unit extraction testing of beverage equipment	B1
B.1	Purpose	B1
B.2	Preparation of exposure water.....	B1
B.3	Exposure protocol	B1
C	Supplemental requirements for marine food equipment.....	C1
C.1	Materials.....	C1
C.2	Design and construction	C1

D

D.1	Summary.....	D1
D.2	Equipment.....	D1
D.3	Microorganism.....	D1
D.4	Supplies	D1
D.5	Reagents.....	D1
D.6	Safety precautions and hazards	D2
D.7	Growth medium.....	D2
D.8	Culture of <i>E. coli</i>	D3

This page is intentionally blank.

Foreword² (This foreword is not part of ANSI/NSF 4 – 2005e.)

The purpose of this Standard is to establish minimum food protection and sanitation requirements for the materials, design, construction and performance of commercial cooking, rethermalization, and powered hot food holding and transport equipment.

This Standard uses inch-pound units as the primary units with SI (metric) units provided in parentheses for informational purposes. The Joint Committee carried a motion that this convention be adopted in future revisions to this Standard. The SI units provided in parenthesis generally represent a hard conversion of the inch-pound units, meaning that the SI value may have been rounded to provide a reasonable and measurable dimension.

In NSF/ANSI 4 – 2005e, the requirements for **5.34 Cappuccino machines with milk reservoirs** was inadvertently left out. In NSF/ANSI 4 – 2005e, the incorrect test method and acceptance criteria for **6.2 Open top hot food holding equipment** was inserted.

5.34 Cappuccino machines with milk reservoirs

5.34.1 Except as noted in 5.34.2, milk reservoirs and all milk-conveying components on cappuccino machines shall conform to the temperature performance criteria of NSF/ANSI 18.

5.34.2 The requirements in 5.34.1 shall not apply to tubing used to convey milk, provided the tubing is:

- designed such that it is completely drained of milk between uses;
- transparent enough to verify that it is void of milk; and
- no greater than 18 in (46 cm) in length.

5.34.3 Milk reservoirs and all milk conveying components, including tubing, shall conform to 5.1.3.

6.2.2 Test method

6.2.2.1 The performance of open hot food holding equipment shall be evaluated within a test chamber maintained under the following conditions for the duration of the test:

- ambient temperature of 73 ± 3 °F (23 ± 2 °C), as measured approximately 10 in (250 mm) from test unit and 36 in (90 cm) from the floor;
- no vertical temperature gradient exceeding 1.5 °F per foot (2.5 °C per meter); and
- maximum air current velocity of 50 ft/min (15.2 m/min) across the surfaces of the test pans.

6.2.2.2 The test unit shall be preheated in accordance with the manufacturer's operating instructions before loading the unit. The test unit shall be loaded with pans of test media prepared and conditioned in accordance with annex A, section A.1 (including proper thermocouple placement). The time required to transfer a single pan from the oven/holding cabinet to the test unit shall not exceed 5 min. Care should be taken to limit the disturbance of the test media during transfer of the pans.

The test unit shall be loaded to the maximum capacity recommended by the manufacturer. If a unit is comprised of multiple, identical hot food holding wells that are individually heated and have separate controls, only

² The information contained in this Disclaimer is not part of this American National Standard (ANS) and has not been processed in accordance with ANSI's requirements for an ANS. As such, this Disclaimer may contain material that has not been subjected to public review or a consensus process. In addition, it does not contain requirements necessary for conformance to the Standard.

a single well shall be loaded and tested. The remaining identical wells shall be kept empty and shall not be operational during the test.

Pan covers shall be removed before the start of the test.

6.2.2.3 The temperature at each thermocouple location shall be monitored immediately upon placing the pans into the unit. The test shall be started upon verification that the media temperature at all thermocouple locations is 150 °F (65 °C) or greater (see the note below regarding temperature stabilization). The temperature at each thermocouple location shall be recorded at 5-min intervals over a test period of 2 h.

NOTE – If the temperature at any thermocouple location drops below 150 °F (65 °C) within 20 min of placing the media in the test unit, the start of the 2-h test period may be delayed until all temperatures are 150 °F (65 °C) or greater. The test period shall start no later than 20 min after the media has been placed in the test unit. The test shall be stopped if the temperature at any thermocouple location is less than 150 °F (65 °C) at the 20-min mark or if a temperature of less than 140 °F (60 °C) is recorded at any time.

6.2.3 Acceptance criteria

The media temperature at each thermocouple location shall be 150 °F (65 °C) or greater throughout the 2-h test period.

In the previous edition of NSF/ANSI 4, the in-place cleaning (IPC) performance evaluation method prescribed two distinct methodologies and acceptance criteria to evaluate a manufacturer's IPC procedures, both of which had to be met for a unit to be deemed acceptable. These were 1) a pour plating technique using Violet Red Bile agar (VRB), which was used primarily for confirmation that the organisms recovered were, in fact, the challenge organisms, and 2) the Most Probable Number (MPN) method using Brilliant Green Bile media, which was used for enumeration of the organisms.

In the version of NSF/ANSI 4 (NSF/ANSI 4 – 2005), the MPN evaluation method used for the IPC evaluation has been replaced with the Membrane Filtration (MF) technique. The MF method also serves as an alternative to both the MPN and the pour plate methodologies. The MPN method has been deemed outdated for this application.

MF is a more sensitive method of determination. The volume of sample analyzed post-IPC is equal to the volume collected (500 mL). Per this method, the entire slug of effluent collected is analyzed (as opposed to the MPN method which employs statistical interpolation to determine the amount of organisms *most probably* present in the entire slug from aliquots thereof). Also, the use of MF makes pour plating with VRB agar procedurally obsolete as the MF technique utilizes a media selective only for the enumeration of the challenge organism.

MF provides a more accurate assessment of the efficacy of the IPC procedure. As such, the NSF Joint Committee on Food Equipment and the NSF Council of Public Health Consultants recommends that NSF/ANSI 4 incorporate the most suitable methodologies and up-to-date techniques commonly available to microbiologists for these evaluations and that this methodology be utilized for the IPC performance evaluations.

A hot-holding performance test has been included for open heated merchandiser units, which will reduce the likelihood of potentially hazardous foods being held out of temperature. Other revisions include: editorial changes to clarify requirements, achieve consistency with the "boilerplate" language in the NSF food equipment standards and update the normative references.

This Standard was developed by the NSF Joint Committee on Food Equipment using the consensus process described by the American National Standards Institute.

Suggestions for improvement of this Standard are welcome. Comments should be sent to Chair, Joint Committee on Food Equipment, c/o NSF International, Standards Department, P.O. Box 130140, Ann Arbor, Michigan, 48113-0140, USA.

NSF/ANSI International Standard
for Food Equipment —

Commercial cooking, rethermalization,
and powered hot food holding
and transport equipment

1 General

1.1 Purpose

This Standard establishes minimum food protection and sanitation requirements for the materials, design, construction, and performance of commercial cooking, rethermalization, and hot food holding and transport equipment and their related components. This Standard does not contain safety requirements.

1.2 Scope

Equipment covered by this Standard includes, but is not limited to, ranges, ovens, fat/oil fryers, fat/oil filters, griddles, tilting griddle skillets, broilers, steam and pressure cookers, kettles, rotisseries, toasters, coffee makers and other hot beverage makers, component water heating equipment, proofing boxes and cabinets, hot food holding equipment, rethermalization equipment, and hot food transport cabinets.

Section 7 of this Standard pertains to food handling and processing equipment that has been designed and manufactured for special use purposes. Food equipment designed and manufactured with a security package is utilized in environments such as correctional facilities, mental health facilities, or some schools. For these environments, where both sanitation and security are concerns, 7 contains exceptions to this Standard that shall only be applicable to the splash and nonfood zones of food equipment provided with a security package.

Equipment components and materials covered under other NSF or NSF/ANSI Standards or Criteria shall also comply with the requirements within. This Standard is not intended to restrict new unit design, provided such design meets the minimum specifications described herein.

1.3 Alternative materials, design, and construction

While specific materials, design, and construction may be stipulated in this Standard, equipment that incorporates alternate materials, design, or construction may be acceptable when such equipment meets the intent of the applicable requirements herein.

1.4 Measurement

Decimal and SI conversions provided parenthetically shall be considered equivalent. Metric conversions have been made according to IEEE/ASTM SI 10.