

rfc0791.txt

RFC: 791

INTERNET PROTOCOL  
DARPA INTERNET PROGRAM  
PROTOCOL SPECIFICATION

September 1981

prepared for  
Defense Advanced Research Projects Agency  
Information Processing Techniques Office  
1400 Wilson Boulevard  
Arlington, Virginia 22209

by  
Information Sciences Institute  
University of Southern California  
4676 Admiralty Way  
Marina del Rey, California 90291

September 1981

Internet Protocol

TABLE OF CONTENTS

PREFACE ..... iii

rfc0791.txt

1.	INTRODUCTI ON .....	1
1.1	Moti vati on .....	1
1.2	Scope .....	1
1.3	Interfaces .....	1
1.4	Operati on .....	2
2.	OVERVI EW .....	5
2.1	Rel ati on to Other Protocols .....	9
2.2	Model of Operati on .....	5
2.3	Functi on Descri pti on .....	7
2.4	Gateways .....	9
3.	SPECI FI CATI ON .....	11
3.1	Internet Header Format .....	11
3.2	Di scussi on .....	23
3.3	Interfaces .....	31
APPENDIX A:	Exampl es & Scenari os .....	34
APPENDIX B:	Data Transmi ssi on Order .....	39
GLOSSARY	.....	41
REFERENCES	.....	45

rfc0791.txt

[Page ii]

September 1981

Internet Protocol

#### PREFACE

This document specifies the DoD Standard Internet Protocol. This document is based on six earlier editions of the ARPA Internet Protocol Specification, and the present text draws heavily from them. There have been many contributors to this work both in terms of concepts and in terms of text. This edition revises aspects of addressing, error handling, option codes, and the security, precedence, compartments, and handling restriction features of the internet protocol.

rfc0791.txt

Jon Postel  
Editor

[Page iii]

September 1981

RFC: 791  
Replaces: RFC 760  
IENs 128, 123, 111,  
80, 54, 44, 41, 28, 26

INTERNET PROTOCOL  
DARPA INTERNET PROGRAM  
PROTOCOL SPECIFICATION

1. INTRODUCTION

1.1. Motivation

The Internet Protocol is designed for use in interconnected systems of  
Page 4

rfc0791.txt

packet-switched computer communication networks. Such a system has been called a "catenet" [1]. The internet protocol provides for transmitting blocks of data called datagrams from sources to destinations, where sources and destinations are hosts identified by fixed length addresses. The internet protocol also provides for fragmentation and reassembly of long datagrams, if necessary, for transmission through "small packet" networks.

## 1.2. Scope

The internet protocol is specifically limited in scope to provide the functions necessary to deliver a package of bits (an internet datagram) from a source to a destination over an interconnected system of networks. There are no mechanisms to augment end-to-end data reliability, flow control, sequencing, or other services commonly found in host-to-host protocols. The internet protocol can capitalize on the services of its supporting networks to provide various types and qualities of service.

## 1.3. Interfaces

This protocol is called on by host-to-host protocols in an internet environment. This protocol calls on local network protocols to carry the internet datagram to the next gateway or destination host.

For example, a TCP module would call on the internet module to take a TCP segment (including the TCP header and user data) as the data portion of an internet datagram. The TCP module would provide the addresses and other parameters in the internet header to the internet module as arguments of the call. The internet module would then create an internet datagram and call on the local network interface to transmit the internet datagram.

In the ARPANET case, for example, the internet module would call on a

[Page 1]

September 1981

## Internet Protocol Introduction

local net module which would add the 1822 header [2] to the internet datagram creating an ARPANET message to transmit to the IMP. The ARPANET address would be derived from the internet address by the local network interface and would be the address of some host in the ARPANET, that host might be a gateway to other networks.

## 1.4. Operation

The internet protocol implements two basic functions: addressing and fragmentation.

The internet modules use the addresses carried in the internet header to transmit internet datagrams toward their destinations. The selection of a path for transmission is called routing.

The internet modules use fields in the internet header to fragment and reassemble internet datagrams when necessary for transmission through "small packet" networks.