



***Society of Cable
Telecommunications
Engineers***

**ENGINEERING COMMITTEE
Interface Practices Subcommittee**

AMERICAN NATIONAL STANDARD

ANSI/SCTE 03 2008

**Test Method for Coaxial Cable
Structural Return Loss**

NOTICE

The Society of Cable Telecommunications Engineers (SCTE) Standards are intended to serve the public interest by providing specifications, test methods and procedures that promote uniformity of product, interchangeability and ultimately the long term reliability of broadband communications facilities. These documents shall not in any way preclude any member or non-member of SCTE from manufacturing or selling products not conforming to such documents, nor shall the existence of such standards preclude their voluntary use by those other than SCTE members, whether used domestically or internationally.

SCTE assumes no obligations or liability whatsoever to any party who may adopt the Standards. Such adopting party assumes all risks associated with adoption of these Standards, and accepts full responsibility for any damage and/or claims arising from the adoption of such Standards.

Attention is called to the possibility that implementation of this standard may require the use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. SCTE shall not be responsible for identifying patents for which a license may be required or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Patent holders who believe that they hold patents which are essential to the implementation of this standard have been requested to provide information about those patents and any related licensing terms and conditions. Any such declarations made before or after publication of this document are available on the SCTE web site at <http://www.scte.org>.

All Rights Reserved

© Society of Cable Telecommunications Engineers, Inc. 2008
140 Philips Road
Exton, PA 19341

TABLE OF CONTENTS

1.0	SCOPE AND DEFINITIONS.....	1
2.0	TEST SAMPLES.....	2
3.0	EQUIPMENT - VARIABLE BRIDGE METHOD.....	2
4.0	MEASUREMENT METHODOLOGY – VARIABLE BRIDGE.....	3
5.0	INSPECTION.....	5
6.0	EQUIPMENT – FIXED BRIDGE METHOD.....	5
7.0	MEASUREMENT METHODOLOGY – FIXED BRIDGE.....	6
8.0	INSPECTION.....	9
9.0	REPORT.....	9
10.0	ERROR ANALYSIS.....	10

1.0 SCOPE AND DEFINITIONS

1.1 SCOPE

- 1.1.1 The purpose of this procedure is to provide instructions to measure cable structural return loss (SRL). There are two test methods presented, as the accuracy, ease-of-use, and required test equipment differs for each test method. The two methods, with their major advantages and deficiencies, are described below:
- 1.1.2 Variable Bridge Method: The return loss of a cable is measured, while varying the impedance of a reflection bridge, until the return loss is minimized. This method requires simple, magnitude only (scalar) measurements, but is subject to errors from the cable connection, and operator skill.
- 1.1.3 Fixed Bridge Method: The cable impedance as a function of frequency is calculated from a vector (magnitude and phase) return loss. The average of this impedance across the desired frequency range is the "cable reference impedance." The structural return loss is calculated from the cable impedance as a function of frequency and the cable reference impedance. This may be automated, but requires a vector network analyzer, and may be subject to errors due to the cable connection

1.2 DEFINITIONS

- 1.2.1 Structural Return Loss (SRL): The return loss of the cable relative to its own impedance.
- 1.2.2 Return Loss: The ratio of reflected signal to incident signal, expressed in dB.
- 1.2.3 Bridge: A device for separating the incident and reflected signals in a return loss measurement.
- 1.2.4 Network Analyzer: An instrument for measuring the swept frequency response of a cable.