



***Society of Cable
Telecommunications
Engineers***

**ENGINEERING COMMITTEE
Interface Practices Subcommittee**

AMERICAN NATIONAL STANDARD

ANSI/SCTE 06 2015

Composite Distortion Measurements (CSO & CTB)

NOTICE

The Society of Cable Telecommunications Engineers (SCTE) Standards are intended to serve the public interest by providing specifications, test methods and procedures that promote uniformity of product, interchangeability and ultimately the long term reliability of broadband communications facilities. These documents shall not in any way preclude any member or non-member of SCTE from manufacturing or selling products not conforming to such documents, nor shall the existence of such standards preclude their voluntary use by those other than SCTE members, whether used domestically or internationally.

SCTE assumes no obligations or liability whatsoever to any party who may adopt the Standards. Such adopting party assumes all risks associated with adoption of these Standards, and accepts full responsibility for any damage and/or claims arising from the adoption of such Standards.

Attention is called to the possibility that implementation of this standard may require the use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. SCTE shall not be responsible for identifying patents for which a license may be required or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Patent holders who believe that they hold patents which are essential to the implementation of this standard have been requested to provide information about those patents and any related licensing terms and conditions. Any such declarations made before or after publication of this document are available on the SCTE web site at <http://www.scte.org>.

All Rights Reserved

© Society of Cable Telecommunications Engineers, Inc. 2015
140 Philips Road
Exton, PA 19341

TABLE OF CONTENTS

| | | |
|-----|--|---|
| 1.0 | SCOPE | 1 |
| 2.0 | DEFINITIONS..... | 1 |
| 3.0 | NORMATIVE REFERENCES | 2 |
| 4.0 | INFORMATIVE REFERENCES..... | 2 |
| 5.0 | EQUIPMENT | 2 |
| 6.0 | SET-UP..... | 3 |
| 7.0 | PROCEDURE..... | 3 |
| | APPENDIX A: FREQUENCY RANDOMIZATION..... | 6 |

LIST OF FIGURES

| | |
|---------------------------------|---|
| FIGURE 1 – TEST EQUIPMENT SETUP | 3 |
|---------------------------------|---|

LIST OF TABLES

| | |
|--------------------|---|
| TABLE 1 – SETTINGS | 4 |
|--------------------|---|

1.0 SCOPE

This document describes a test procedure for the laboratory and production measurement of composite distortion products. There are two types of composite distortions considered: Composite Second Order and Composite Triple Beat. In order to obtain a stable, repeatable measurement, this test procedure describes testing performed with continuous wave (CW) carriers. See ANSI/SCTE 96 2008 for a discussion of the selection of CW carrier frequencies.

2.0 DEFINITIONS

Discrete Second Order (DSO): An individual, second order intermodulation product, produced when one or two carriers pass through a non-linear component.

Composite Second Order (CSO): The sum of all DSO products that happen to fall at the same nominal frequency in a multi-tone system. CSO is defined as the difference, in dB, between the rms voltage of the carrier measured at its peak and the rms voltage of this sum. This procedure describes a technique for measuring this difference using a spectrum analyzer (SA) in the LOG mode. For consistency with existing measurements and specifications, the results of measurements made using any other technique must be correlated with the results from this technique.

Discrete Third Order (DTO): An individual, third order intermodulation product, produced when one, two or three carriers pass through a non-linear component.

Composite Triple Beat (CTB): The sum of all DTO products in a multi-tone system that happen to fall at the same nominal frequency in a multi-tone system. CTB is defined as the difference, in dB, between the rms voltage of the carrier measured at its peak and the rms voltage of this sum. As with CSO, this procedure describes a technique for measuring this difference using a SA in the LOG mode. For consistency with existing measurements and specifications, the results of measurements made using any other technique must be correlated with the results from this technique.

Refer to the Definitions and Acronyms section of ANSI/SCTE 96 2008 for other definitions.