



***Society of Cable  
Telecommunications  
Engineers***

---

**ENGINEERING COMMITTEE**  
**Digital Video Subcommittee**

---

**AMERICAN NATIONAL STANDARD**

**ANSI/SCTE 07 2013**

**Digital Transmission Standard  
For Cable Television**

## NOTICE

The Society of Cable Telecommunications Engineers (SCTE) Standards are intended to serve the public interest by providing specifications, test methods and procedures that promote uniformity of product, interchangeability and ultimately the long term reliability of broadband communications facilities. These documents shall not in any way preclude any member or nonmember of SCTE from manufacturing or selling products not conforming to such documents, nor shall the existence of such standards preclude their voluntary use by those other than SCTE members, whether used domestically or internationally.

SCTE assumes no obligations or liability whatsoever to any party who may adopt the Standards. Such adopting party assumes all risks associated with adoption of these Standards or Recommended Practices, and accepts full responsibility for any damage and/or claims arising from the adoption of such Standards or Recommended Practices.

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. SCTE shall not be responsible for identifying patents for which a license may be required or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Patent holders who believe that they hold patents which are essential to the implementation of this standard have been requested to provide information about those patents and any related licensing terms and conditions. Any such declarations made before or after publication of this document are available on the SCTE web site at <http://www.scte.org>.

All Rights Reserved

© Society of Cable Telecommunications Engineers, Inc. 2013  
140 Philips Road  
Exton, PA 19341

## Table of Contents

1	Introduction .....	1
2	Symbols and abbreviations .....	1
	2.1 Symbols .....	1
	2.2 Abbreviations .....	1
3	Cable system concept .....	2
4	MPEG-2 transport framing .....	3
5	Forward error correction .....	7
	5.1 Reed-Solomon coding .....	7
	5.2 Interleaving .....	8
	5.3 Frame synchronization sequence .....	10
	5.4 Randomization .....	11
	5.5 Trellis coded modulation .....	12
6	Modulation and demodulation .....	18
	6.1 QAM characteristics .....	18
	6.2 QAM modulator RF output .....	18
7	References .....	19
	ANNEX A (INFORMATIVE) Calculation of Concatenated Code Rate for QAM Cable Transmission .....	20

Note: this edition of SCTE 07 contains no substantive changes compared to the 2006 edition.

This is a preview of "ANSI/SCTE 07 2013". [Click here to purchase the full version from the ANSI store.](#)

## 1 Introduction

This standard describes the framing structure, channel coding, and channel modulation for a digital multi-service television distribution system that is specific to a cable channel. The system can be used transparently with the distribution from a satellite channel, as many cable systems are fed directly from satellite links. The specification covers both 64 and 256 QAM. Most features of both modulation schemes are the same. Where there are differences, the specific details for each modulation scheme is covered.

The design of the modulation, interleaving and coding is based upon testing and characterization of cable systems in North America. The modulation is Quadrature Amplitude Modulation with a 64 point signal constellation (64-QAM) and with a 256 point signal constellation (256-QAM), transmitter selectable. The forward error correction (FEC) is based on a concatenated coding approach that produces high coding gain at moderate complexity and overhead. Concatenated coding offers improved performance over a block code, at a similar overall complexity. The system FEC is optimized for quasi error free operation at a threshold output error event rate of one error event per 15 minutes.

The data format input to the modulation and coding is assumed to be MPEG-2 transport. However, the method used for MPEG synchronization is decoupled from FEC synchronization. For example, this enables the system to carry Asynchronous Transfer Mode (ATM) packets easily without interfering with ATM synchronization. In fact, ATM synchronization may be performed by defined ATM synchronization mechanisms.

There are two modes supported: Mode 1 has a symbol rate of 5.057 Msps and Mode 2 has a symbol rate of 5.361 Msps. Typically, Mode 1 will be used for 64-QAM and Mode 2 will be used for 256-QAM. The system will be compatible with future implementations of higher data rate schemes employing higher order QAM extensions.

## 2 Symbols and abbreviations

### 2.1 SYMBOLS

For the purposes of this Recommendation, the following symbols are used:

$\alpha$	Roll-off factor
byte	Eight bits
bps	Bits per second
$g(x)$	RS code generator polynomial
ms	millisecond
$p(x)$	RS field generator polynomial
$q$	Number of bits: 2, 3, 4 for 16-QAM, 32-QAM, 64-QAM, respectively
$T$	Number of bytes which can be corrected in RS error-protected packet

### 2.2 ABBREVIATIONS

For the purposes of this Recommendation, the following abbreviations are used:

ATM	Asynchronous Transfer Mode
FEC	Forward Error Correction
HEC	Header Error Control
HEX	Hexadecimal
LSB	Least Significant Bit
MPEG	Motion Picture Expert-Group
MSB	Most Significant Bit