



**SOCIETY OF CABLE
TELECOMMUNICATIONS
ENGINEERS, INC.**

ENGINEERING COMMITTEE
Data Standards Subcommittee

AMERICAN NATIONAL STANDARD

ANSI/SCTE 137-2 2007

DOCSIS Downstream External PHY Interface for Modular

NOTICE

The Society of Cable Telecommunications Engineers (SCTE) Standards are intended to serve the public interest by providing specifications, test methods and procedures that promote uniformity of product, interchangeability and ultimately the long term reliability of broadband communications facilities. These documents shall not in any way preclude any member or non-member of SCTE from manufacturing or selling products not conforming to such documents, nor shall the existence of such standards preclude their voluntary use by those other than SCTE members, whether used domestically or internationally.

SCTE assumes no obligations or liability whatsoever to any party who may adopt the Standards. Such adopting party assumes all risks associated with adoption of these Standards, and accepts full responsibility for any damage and/or claims arising from the adoption of such Standards.

Attention is called to the possibility that implementation of this standard may require the use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. SCTE shall not be responsible for identifying patents for which a license may be required or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Patent holders who believe that they hold patents which are essential to the implementation of this standard have been requested to provide information about those patents and any related licensing terms and conditions. Any such declarations made before or after publication of this document are available on the SCTE web site at <http://www.scte.org>.

All Rights Reserved

© Society of Cable Telecommunications Engineers, Inc. 2007
140 Philips Road
Exton, PA 19341

Contents

1	SCOPE	1
2	REFERENCES.....	1
2.1	NORMATIVE REFERENCES	1
2.2	INFORMATIVE REFERENCES.....	2
2.3	REFERENCE ACQUISITION	2
3	TERMS AND DEFINITIONS	2
4	ABBREVIATIONS, ACRONYMS AND CONVENTIONS.....	5
4.1	ABBREVIATIONS AND ACRONYMS	5
4.2	CONVENTIONS	8
5	TECHNICAL OVERVIEW	8
5.1	SYSTEM ARCHITECTURE	9
5.1.1	<i>Reference Architecture</i>	9
5.1.2	<i>DEPI Operation</i>	10
5.1.3	<i>EQAM Operation</i>	11
5.2	BONDING SERVICES MODEL.....	12
5.3	MULTIPLE SERVICES MODEL	12
6	DEPI ARCHITECTURE.....	13
6.1	DEPI DATA PATH	13
6.1.1	<i>DOCSIS D-MPT Data Path</i>	14
6.1.2	<i>PSP Data Path</i>	14
6.1.3	<i>DOCSIS SYNC Message</i>	14
6.1.4	<i>Latency and Skew Requirements</i>	16
6.2	NETWORKING CONSIDERATIONS	17
6.2.1	<i>Per Hop Behavior Usage</i>	17
6.2.2	<i>DiffServ Code Point Usage</i>	17
6.2.3	<i>Packet Sequencing</i>	17
6.2.4	<i>Network MTU</i>	18
6.3	SYSTEM TIMING CONSIDERATIONS	18
7	DEPI CONTROL PLANE	18
7.1	TOPOLOGY	19
7.2	ADDRESSING	19
7.3	CONTROL MESSAGE FORMAT.....	21
7.3.1	<i>Control Message with a UDP Header</i>	22
7.3.2	<i>Control Message without a UDP Header</i>	23
7.3.3	<i>Common Headers for Control and Data Messages</i>	23
7.3.4	<i>Specific Headers for Control Messages</i>	24
7.4	SIGNALING	25
7.4.1	<i>Control Connection Signaling</i>	26
7.4.2	<i>Session Signaling</i>	28
7.4.3	<i>Required and Optional AVPs</i>	30
7.5	AVP DEFINITIONS	31
7.5.1	<i>Conventional L2TPv3 AVPs</i>	31
7.5.2	<i>DEPI Specific AVPs</i>	36
7.5.3	<i>QAM Channel PHY AVPs</i>	41
8	DEPI FORWARDING PLANE	45
8.1	L2TPv3 TRANSPORT PACKET FORMAT.....	45
8.1.1	<i>Data Message with a UDP Header</i>	46

8.1.2	<i>Data Message without a UDP Header</i>	47
8.1.3	<i>Specific Headers for Data Messages</i>	47
8.2	DOCSIS MPT MODE	48
8.3	PSP MODE	49
8.4	DEPI LATENCY MEASUREMENT (DLM) SUB-LAYER HEADER	50
8.5	M-CMTS CORE OUTPUT RATE	51
ANNEX A	DEPI MTU	52
A.1	L2TPv3 LOWER LAYER PAYLOAD SIZE.....	52
A.2	MAXIMUM FRAME SIZE FOR DEPI	52
A.3	PATH MTU DISCOVERY	52
ANNEX B	PARAMETERS AND CONSTANTS.....	54
APPENDIX I	DEPI AND DOCSIS SYSTEM PERFORMANCE.....	55
I.1	INTRODUCTION	55
I.2	ROUND-TRIP TIME AND PERFORMANCE.....	55
I.3	ELEMENTS OF ROUND-TRIP TIME	55
I.4	CIN CHARACTERISTICS.....	57
I.5	QUEUEING DELAYS IN NETWORK ELEMENTS.....	58
I.6	TRAFFIC PRIORITIZATION AND NETWORK DELAYS.....	59
I.7	QUEUE PERSISTENCE IN A DEPI FLOW	59
I.8	PSP MODE	61
APPENDIX II	EARLY ADOPTION AND EVOLVING USE OF EQAM DEVICES	62
II.1	EQAM DEVELOPMENT: CATEGORY A (NO DTI).....	62
II.2	EQAM DEVELOPMENT: CATEGORY B (WITH DTI)	62
II.3	POSSIBLE M-CMTS FEATURE PHASING	62
II.4	OPTIONAL UDP LAYER	63

List of Figures

FIGURE 5–1 - MODULAR CMTS REFERENCE ARCHITECTURE.....	9
FIGURE 5–2 - EQAM BLOCK DIAGRAM	11
FIGURE 5–3 - BONDING SERVICES MODEL	12
FIGURE 5–4 - MULTI-SERVICE MODE.....	12
FIGURE 6–1 - DOWNSTREAM EQAM BLOCK DIAGRAM	13
FIGURE 6–2 - FORMAT OF A DOCSIS SYNC MAC MESSAGE	15
FIGURE 7–1 - L2TP TOPOLOGY FOR MODULAR CMTS.....	19
FIGURE 7–2 - DEPI ADDRESSING HIERARCHY	20
FIGURE 7–3 - DEPI ADDRESSING HIERARCHY	20
FIGURE 7–4 - DEPI CONTROL PACKET WITH UDP	22
FIGURE 7–5 - DEPI CONTROL PACKET WITHOUT UDP	23
FIGURE 7–6 - DEPI CONTROL CONNECTION SETUP	26
FIGURE 7–7 - DEPI CONTROL CONNECTION TEARDOWN	27
FIGURE 7–8 - DEPI KEEP-ALIVE	28
FIGURE 7–9 - DEPI SESSION SETUP	28
FIGURE 7–10 - DEPI SESSION TEARDOWN	29
FIGURE 7–11 - DEPI SESSION UPDATES.....	30
FIGURE 7–12 - MESSAGE TYPE AVP.....	32
FIGURE 7–13 - RESULT CODE AVP	32
FIGURE 7–14 - HOST NAME AVP	33
FIGURE 7–15 - VENDOR NAME AVP	33
FIGURE 7–16 - SERIAL NUMBER AVP	33
FIGURE 7–17 - ROUTER ID AVP	33
FIGURE 7–18 - CONTROL CONNECTION ID AVP	34
FIGURE 7–19 - PSEUDOWIRE CAPABILITIES LIST AVP	34
FIGURE 7–20 - LOCAL SESSION ID AVP	34
FIGURE 7–21 - REMOTE SESSION ID AVP	35
FIGURE 7–22 - REMOTE END ID AVP	35
FIGURE 7–23 - PSEUDOWIRE TYPE AVP	35
FIGURE 7–24 - L2-SPECIFIC SUBLAYER AVP	35
FIGURE 7–25 - DATA SEQUENCING AVP	36
FIGURE 7–26 - CIRCUIT STATUS AVP	36
FIGURE 7–27 - DEPI RESULT AND ERROR CODE AVP	37
FIGURE 7–28 - DEPI RESOURCE ALLOCATION REQUEST AVP	37
FIGURE 7–29 - DEPI RESOURCE ALLOCATION REPLY AVP	38
FIGURE 7–30 - DEPI LOCAL MTU AVP	39
FIGURE 7–31 - DOCSIS SYNC AVP	39
FIGURE 7–32 - EQAM CAPABILITIES AVP	40
FIGURE 7–33 - DEPI REMOTE MTU MAX PAYLOAD AVP	40
FIGURE 7–34 – LOCAL UDP PORT AVP.....	40
FIGURE 7–35 - TSID GROUP AVP	41
FIGURE 7–36 - FREQUENCY AVP	42
FIGURE 7–37 - POWER AVP	42
FIGURE 7–38 - MODULATION AVP	42
FIGURE 7–39 - J.83 ANNEX AVP	43
FIGURE 7–40 - SYMBOL RATE AVP	43
FIGURE 7–41 - INTERLEAVER DEPTH AVP	44
FIGURE 7–42 - RF MUTE AVP	44
FIGURE 8–1 - L2TPv3 DATA PACKET OUTER ENCAPSULATION WITH UDP	46
FIGURE 8–2 - L2TPv3 DATA PACKET OUTER ENCAPSULATION WITHOUT UDP	47
FIGURE 8–3 - DOCSIS MPT SUB-LAYER HEADER AND PAYLOAD	48
FIGURE 8–4 - DEPI PSP SUB-LAYER HEADER AND PAYLOAD	49

FIGURE 8–5 - DLM SUB-LAYER HEADER	50
---	----

List of Tables

TABLE 7–1 - DEPI CONTROL MESSAGES	25
TABLE 7–2 - DEPI MANDATORY AND OPTIONAL AVPs	30
TABLE 7–3 - DEPI SUPPORTED L2TPv3 AVPs.....	31
TABLE 7–4 - PSEUDOWIRE TYPES.....	34
TABLE 7–5 - L2-SPECIFIC SUBLAYER TYPES.....	36
TABLE 7–6 - DEPI DEFINED GENERAL SESSION APVs.....	36
TABLE 7–7 - DEPI DEFINED QAM CHANNEL PHY AVPs.....	41
TABLE A–1 - MTU OF DEPI	52
TABLE B–1 - PARAMETERS AND CONSTANTS.....	54
TABLE I–1 - DOCSIS REQUEST-GANT ROUND TRIP WORKSHEET.....	57

1 SCOPE

This Standard is part of the DOCSIS® family of Standards that define a Modular Cable Modem Termination System (M-CMTS™) architecture for head-end components that comply with DOCSIS.

The DOCSIS Standards[DOCSIS-RFI] define the requirements for the two fundamental components that comprise a high-speed data-over-cable system: the cable modem (CM) and the cable modem termination system (CMTS). The M-CMTS architecture was designed as an extension to the DOCSIS Standards to allow for flexibility and independent scaling of certain CMTS functions, and to allow operators to more efficiently use available network resources.

One of the key elements of the M-CMTS architecture is the separation of the downstream physical layer QAM modulation and up-conversion functions from the CMTS, and the placement of that functionality into an "Edge-QAM" (EQAM) device. This separation allows for the development of EQAM products that support both video and DOCSIS, which in turn allows operators to use the same network resources to support multiple types of services such as data, voice, and video.

This document defines an interface known as the Downstream External PHY Interface (DEPI) and associated protocol requirements for the transport of downstream user data between the "M-CMTS Core" and the EQAM. It describes the characteristics of the DEPI interface, provides requirements that must be met by the M-CMTS Core and the EQAM, and also describes various aspects of technical issues that are involved in the implementation and deployment of a DOCSIS system using the M-CMTS architecture.

A list of the documents in the Modular CMTS Interface Standards family is provided below.

{Editor's note: To be updated to SCTE standards when designations are available}

Designation	Title
SCTE 137-2 2007	DOCSIS Downstream External PHY Interface for Modular
SCTE 137-1 2007	DOCSIS Timing Interface for Cable Modem Termination Systems
SCTE 139 2007	Edge Resource Manager Interface for Modular Cable Modem Termination Systems
SCTE 141 2007	Operations Support System Interface for Modular Cable Modem Termination Systems

2 REFERENCES

2.1 Normative References

All references are subject to revision; users of this specification are therefore encouraged to investigate the possibility of applying the most recent edition of the standards and other references listed below.

- [DOCSIS-RFI] ANSI/SCTE 79-1 2003 (formerly DSS 02-01) DOCS 2.0 Part 1: Radio Frequency Interface
- [SCTE 133] Downstream RF Interface for Cable Modem Termination Systems. 2007
- [SCTE 137-1] DOCSIS Timing Interface for Cable Modem Termination Systems, 2007.
- [IANA-PORTS] IANA, "Port Numbers", June 29, 2004.
- [IEEE-802.1Q] IEEE Std 802.1Q™-2003, "Virtual Bridged Local Area Networks", May 7, 2003.