

# SCTE • ISBE<sup>®</sup>

# S T A N D A R D S

---

**Interface Practices Subcommittee**

---

**AMERICAN NATIONAL STANDARD**

**ANSI/SCTE 15 2019**

**Specification for Trunk, Feeder and Distribution  
Coaxial Cable**

ANSI/SCTE 15 2019

## NOTICE

The Society of Cable Telecommunications Engineers (SCTE) / International Society of Broadband Experts (ISBE) Standards and Operational Practices (hereafter called “documents”) are intended to serve the public interest by providing specifications, test methods and procedures that promote uniformity of product, interchangeability, best practices and ultimately the long-term reliability of broadband communications facilities. These documents shall not in any way preclude any member or non-member of SCTE•ISBE from manufacturing or selling products not conforming to such documents, nor shall the existence of such standards preclude their voluntary use by those other than SCTE•ISBE members.

SCTE•ISBE assumes no obligations or liability whatsoever to any party who may adopt the documents. Such adopting party assumes all risks associated with adoption of these documents, and accepts full responsibility for any damage and/or claims arising from the adoption of such documents.

Attention is called to the possibility that implementation of this document may require the use of subject matter covered by patent rights. By publication of this document, no position is taken with respect to the existence or validity of any patent rights in connection therewith. SCTE•ISBE shall not be responsible for identifying patents for which a license may be required or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Patent holders who believe that they hold patents which are essential to the implementation of this document have been requested to provide information about those patents and any related licensing terms and conditions. Any such declarations made before or after publication of this document are available on the SCTE•ISBE web site at <http://www.scte.org>.

All Rights Reserved

© Society of Cable Telecommunications Engineers, Inc. 2019  
140 Philips Road  
Exton, PA 19341

## Table of Contents

Title	Page Number
NOTICE	2
Table of Contents	3
1. Introduction	5
1.1. Executive Summary	5
1.2. Scope	5
1.3. Benefits	5
1.4. Intended Audience	5
1.5. Areas for Further Investigation or to be Added in Future Versions	5
2. Normative References	5
2.1. SCTE References	5
2.2. Standards from Other Organizations	6
2.3. Published Materials	6
3. Informative References	6
3.1. SCTE References	6
3.2. Standards from Other Organizations	6
3.3. Published Materials	7
4. Compliance Notation	7
5. Center Conductor	7
5.1. Material	7
5.2. Joints	7
5.3. Dimensions	8
5.4. DC Resistance	8
6. Foam Dielectric	8
6.1. Foam Dielectric Material	8
6.2. Patching	8
7. Disc And Air Dielectric	9
7.1. Disc and Air Dielectric Material	9
7.2. Patching	9
8. Outer Conductor (Shield)	9
8.1. Material	9
8.2. Outer Conductor Dimensions	9
8.3. Dielectric Adhesion to Outer Conductor	10
9. Outer Conductor Flooding Compound	10
9.1. Material	10
10. Cable Jacket	10
10.1. Material	10
10.2. Diameter Over Jacket (DOJ)	11
10.3. Jacket Thickness	11
10.4. Jacket Eccentricity	12
11. Integral Messenger	12
11.1. Material	12
11.2. Joints	12
12. Armor	12
12.1. Material	12
12.2. Armor Construction	12
12.3. Outer Jacket	12
13. Finished Product Mechanical Tests	13
13.1. PE Jacket Longitudinal Shrinkage	13
13.2. Dielectric Shrinkback	13
13.3. Dielectric Shear Adhesion	13
13.4. Air Leakage Test	13

ANSI/SCTE 15 2019

13.5.	Thermal Oxidative Stability	13
13.6.	Cable Static Minimum Bend	14
13.7.	Cable Static Pull Force	14
14.	Finished Product Electrical Tests	14
14.1.	Spark Test	14
14.2.	Characteristic Impedance	14
14.3.	Conductor Resistance	14
14.4.	Velocity of Propagation (VOP)	15
14.5.	Structural Return Loss (SRL)	15
14.6.	Attenuation	15

### List of Tables

<b>Title</b>	<b>Page Number</b>
Table 1 – Center Conductor Dimensions [Inch (mm)]	8
Table 2 – Outer Conductor Dimensions [Inch (mm)]	9
Table 3 – Jacket Material Requirements	10
Table 4 – Nominal Diameter over Jacket [Inch (mm)]	11
Table 5 – Minimum Jacket Thickness [Inch (mm)]	11
Table 6 – Foam Dielectric and Disc Adhesion to Center Conductor	13
Table 7 – Maximum DC Resistance at 68 °F (20 °C), ohms/kft (ohms/km)	14
Table 8 – Maximum Attenuation at 68 °F (20 °C), dB/100 ft. (dB/100m)	15
Table 9 – Maximum Attenuation at 68 °F (20 °C), dB/100 ft. (dB/100 m)	15
Table 10 – Maximum Attenuation at 68 °F (20 °C), dB/100 ft. (dB/100 m)	16

ANSI/SCTE 15 2019

## 1. Introduction

### 1.1. Executive Summary

This specification applies to general purpose trunk, feeder and distribution coaxial cables. Currently there are two distinctive designs of dielectric available; gas injected foam dielectric and disc and air dielectric. This document will cover both designs. Specialty cables will not be included in this document.

References to the National Electrical Code, National Electrical Safety Code, ASTM and other regulations or specifications should adhere to the latest document and should keep current with each document.

This specification in no way should limit or restrict any manufacture's innovations and improvement. Innovation and improvements are encouraged, and this specification may be adjusted when beneficial.

### 1.2. Scope

This specification applies to material, electrical and mechanical properties of seventy-five-ohm coaxial cables as defined herein. Seventy-five-ohm coaxial cables are used to distribute radio frequency (R.F.), digital signals and power as applicable.

### 1.3. Benefits

- This standard allows for interface between multiple vendors of coax, connectors, tools, equipment and accessories.
- Without this specification the end user would have to pair hardline cable & parts due to lack of standardization.

### 1.4. Intended Audience

The intended audience are mainly manufactures. System operators should also find use in this specification as reference to their products and capabilities.

### 1.5. Areas for Further Investigation or to be Added in Future Versions

DOCSIS 3.1 specifications include operation at frequencies up to 1218 MHz, and optionally, to 1794 MHz. This document includes specifications up to 1218 MHz.

## 2. Normative References

The following documents contain provisions, which, through reference in this text, constitute provisions of this document. At the time of Subcommittee approval, the editions indicated were valid. All documents are subject to revision; and while parties to any agreement based on this document are encouraged to investigate the possibility of applying the most recent editions of the documents listed below, they are reminded that newer editions of those documents might not be compatible with the referenced version.

### 2.1. SCTE References

- ANSI/SCTE 03 2008 – Test Method for Coaxial Cable Structural Return Loss
- ANSI/SCTE 11 2012 – Test Method for Aerial Cable Corrosion Protection Flow
- ANSI/SCTE 12 2011 – Test Method for Center Conductor Bond to Dielectric for Trunk Feeder and Distribution Coaxial Cables