



***Society of Cable  
Telecommunications  
Engineers***

---

**ENGINEERING COMMITTEE  
Network Operations Subcommittee**

---

**AMERICAN NATIONAL STANDARD**

**ANSI/SCTE 25-1 2017**

**Hybrid Fiber Coax Outside Plant Status Monitoring –  
Physical (PHY) Layer Specification v1.**

## NOTICE

The Society of Cable Telecommunications Engineers (SCTE) Standards and Operational Practices (hereafter called “documents”) are intended to serve the public interest by providing specifications, test methods and procedures that promote uniformity of product, interchangeability, best practices and ultimately the long term reliability of broadband communications facilities. These documents shall not in any way preclude any member or non-member of SCTE from manufacturing or selling products not conforming to such documents, nor shall the existence of such standards preclude their voluntary use by those other than SCTE members.

SCTE assumes no obligations or liability whatsoever to any party who may adopt the documents. Such adopting party assumes all risks associated with adoption of these documents, and accepts full responsibility for any damage and/or claims arising from the adoption of such documents.

Attention is called to the possibility that implementation of this document may require the use of subject matter covered by patent rights. By publication of this document, no position is taken with respect to the existence or validity of any patent rights in connection therewith. SCTE shall not be responsible for identifying patents for which a license may be required or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Patent holders who believe that they hold patents which are essential to the implementation of this document have been requested to provide information about those patents and any related licensing terms and conditions. Any such declarations made before or after publication of this document are available on the SCTE web site at <http://www.scte.org>.

All Rights Reserved

© Society of Cable Telecommunications Engineers, Inc. 2017  
140 Philips Road  
Exton, PA 19341

## TABLE OF CONTENTS

<b>LIST OF FIGURES .....</b>	<b>5</b>
<b>LIST OF TABLES .....</b>	<b>6</b>
<b>DOCUMENT HISTORY .....</b>	<b>7</b>
1.1 SCOPE .....	7
1.2 TRANSPONDER TYPE CLASSIFICATIONS .....	7
1.3 HMS REFERENCE ARCHITECTURE FORWARD AND RETURN CHANNEL SPECIFICATIONS .....	9
1.4 HMS SPECIFICATION DOCUMENTS .....	10
1.5 FUNCTIONAL ASSUMPTIONS .....	11
1.5.1 <i>Forward and Return Spectrum</i> .....	11
1.5.2 <i>Transmission Levels</i> .....	11
<b>2 PHYSICAL LAYER SPECIFICATION .....</b>	<b>12</b>
2.1 SEPARATE FORWARD AND RETURN CHANNELS .....	12
2.2 SINGLE FORWARD AND RETURN PATH CHANNELS .....	12
2.3 BYTE-BASED TRANSMISSION.....	12
2.4 BYTE FORMATS AND TRANSMISSION ORDER.....	12
2.5 PACKET-BASED TRANSMISSION.....	13
2.6 DUPLEX OPERATION .....	13
2.7 FORWARD AND RETURN CHANNEL SPECIFICATIONS.....	13
2.7.1 <i>Transmit Power Level</i> .....	15
2.7.2 <i>Transmit Power Accuracy</i> .....	16
2.7.3 <i>Transmit Power Step Size</i> .....	16
2.7.4 <i>Transmitter Frequencies</i> .....	16
2.7.5 <i>Transmitter Frequency Step Size</i> .....	16
2.7.6 <i>Transmitter Frequency Accuracy</i> .....	16
2.7.7 <i>Transmitter Conducted Spurious</i> .....	16
2.7.8 <i>Spectral Shape</i> .....	16
2.7.9 <i>Transmitter Out-of-Band Noise Suppression</i> .....	17
2.7.10 <i>Transmit Nominal Impedance</i> .....	17
2.7.11 <i>Transmit Return Loss</i> .....	17
2.7.12 <i>Maximum Ramp-Up Time</i> .....	17
2.7.13 <i>Maximum Ramp-Down Time</i> .....	17
2.7.14 <i>Transmitter Front Porch Time</i> .....	18
2.7.15 <i>Receive Power Dynamic Range</i> .....	18
2.7.16 <i>Receive Tuning Range</i> .....	18
2.7.17 <i>Receiver Frequency Step Size</i> .....	18
2.7.18 <i>Receive C/(N+I)</i> .....	18
2.7.19 <i>Receiver Selectivity</i> .....	19
2.7.20 <i>Receive Nominal Impedance</i> .....	19
2.7.21 <i>Receive Return Loss</i> .....	19
2.7.22 <i>Transmitter Slew Rate</i> .....	19

2.7.23	<i>Transmitter On/Off Ratio</i> .....	20
2.7.24	<i>Modulation Technique</i> .....	20
2.7.25	<i>Bit Rate</i> .....	20
2.7.26	<i>Bit Rate Accuracy</i> .....	20
2.7.27	<i>Transmitter Power Delta Between ‘Mark’ and ‘Space’</i> .....	20
2.7.28	<i>Transmission Duplexing</i> .....	20
2.7.29	<i>Transmission Mode</i> .....	20
2.7.30	<i>RF Connector</i> .....	20
2.7.31	<i>Operating Temperature Range</i> .....	21
2.8	MEDIA ACCESS CONTROL LAYER INTERFACE .....	21
2.9	RF CUTOFF .....	21
<b>REFERENCES</b> .....		<b>22</b>
<b>3 NORMATIVE REFERENCES</b> .....		<b>22</b>
<b>APPENDIX A. GLOSSARY</b> .....		<b>23</b>
<b>APPENDIX B. LIST OF ACRONYMS</b> .....		<b>25</b>

## LIST OF FIGURES

FIGURE 1: HMS REFERENCE ARCHITECTURE DIAGRAM.....	9
FIGURE 2: BIT TRANSMISSION ORDER.....	13

## LIST OF TABLES

TABLE 1: TRANSPONDER TYPE CLASSIFICATIONS.....	8
TABLE 2: HMS DOCUMENT FAMILY .....	10
TABLE 3: SPECTRAL LIMITS BY GEOGRAPHICAL AREA.....	11
TABLE 4: HMS PHY CHANNEL RF AND MODULATION SPECIFICATIONS.....	14

## Introduction

The Hybrid Fiber Coax (HFC) Outside Plant (OSP) Physical (PHY) Layer Specification is part of the suite of specifications developed by the Hybrid Management Sub-Layer (HMS) subcommittee under the SCTE. The purpose of the HMS specifications is to support the design and implementation of interoperable management systems for evolving HFC cable networks. The HMS Physical (PHY) Layer Specification describes the physical layer portion of the protocol stack used for communication between HMS-compliant transponders interfacing to manage outside plant network elements (NE) and a centralized headend element (HE).

### 1.1 Scope

This specification describes the PHY layer requirements that must be implemented by all *Type 2* and *Type 3* compliant OSP HMS transponders on the HFC plant and the controlling equipment in the headend. Any exceptions to compliance with this specification will be specifically noted in this document as necessary. Refer to **Table 1** for a full definition of the Type Classifications.

#### Note

Electromagnetic Compatibility (EMC) is not specified in this standard and is left to the vendor to ensure compliance with local EMC regulatory requirements. Other than operating temperature, physical parameters such as shock, vibration, humidity, etc., are also not specified and left to the vendor's discretion.

### 1.2 Transponder Type Classifications

Transponder type classifications referenced within the HMS suite of specifications are defined in **Table 1**.