



***Society of Cable
Telecommunications
Engineers***

**ENGINEERING COMMITTEE
Data Standards Subcommittee**

SCTE STANDARD

SCTE 165-18 2016

IPCablecom 1.5 Part 18: CMS to CMS Signaling

NOTICE

The Society of Cable Telecommunications Engineers (SCTE) Standards and Operational Practices (hereafter called “documents”) are intended to serve the public interest by providing specifications, test methods and procedures that promote uniformity of product, interchangeability, best practices and ultimately the long term reliability of broadband communications facilities. These documents shall not in any way preclude any member or non-member of SCTE from manufacturing or selling products not conforming to such documents, nor shall the existence of such standards preclude their voluntary use by those other than SCTE members.

SCTE assumes no obligations or liability whatsoever to any party who may adopt the documents. Such adopting party assumes all risks associated with adoption of these documents, and accepts full responsibility for any damage and/or claims arising from the adoption of such documents.

Attention is called to the possibility that implementation of this document may require the use of subject matter covered by patent rights. By publication of this document, no position is taken with respect to the existence or validity of any patent rights in connection therewith. If a patent holder has filed a statement of willingness to grant a license under these rights on reasonable and nondiscriminatory terms and conditions to applicants desiring to obtain such a license, then details may be obtained from the standards developer. SCTE shall not be responsible for identifying patents for which a license may be required or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Patent holders who believe that they hold patents which are essential to the implementation of this document have been requested to provide information about those patents and any related licensing terms and conditions. Any such declarations made before or after publication of this document are available on the SCTE web site at <http://www.scte.org>.

All Rights Reserved

© Society of Cable Telecommunications Engineers, Inc. 2016
140 Philips Road
Exton, PA 19341

Note: DOCSIS® and PacketCable™ are a registered trademarks of Cable Television Laboratories, Inc., and are used in this document with permission.

Contents

1	INTRODUCTION	1
1.1	SCOPE.....	1
1.2	SPECIFICATION LANGUAGE	2
2	REFERENCES	3
2.1	NORMATIVE REFERENCES	3
2.2	INFORMATIVE REFERENCES.....	5
2.3	REFERENCE ACQUISITION.....	5
3	TERMS AND DEFINITIONS	6
4	ABBREVIATIONS AND ACRONYMS.....	10
5	BACKGROUND AND MOTIVATION	12
5.1	REQUIREMENTS AND DESIGN PRINCIPLES	12
5.2	IPCABLECOM ARCHITECTURE.....	13
5.3	CMSS TRUST MODEL	15
5.4	CMS TO CMS ARCHITECTURAL MODEL.....	16
5.5	OVERVIEW OF CMS BEHAVIOR.....	18
5.6	BASIC TELEPHONY CALL FLOW	19
5.7	CMS-MGC BASIC TELEPHONY CALL FLOW.....	20
6	SIP PROFILE	23
6.1	INTRODUCTION.....	23
6.2	OVERVIEW OF SIP FUNCTIONALITY	23
6.3	TERMINOLOGY	23
6.4	OVERVIEW OF OPERATION	23
6.5	STRUCTURE OF THE PROTOCOL	23
6.6	DEFINITIONS.....	23
6.7	SIP MESSAGES	23
6.7.1	<i>Requests</i>	24
6.7.2	<i>Responses</i>	24
6.7.3	<i>Header Fields</i>	24
6.7.4	<i>Bodies</i>	24
6.7.5	<i>Framing SIP Messages</i>	24
6.8	GENERAL USER AGENT BEHAVIOR	24
6.8.1	<i>UAC Behavior</i>	24
6.8.2	<i>UAS Behavior</i>	25
6.8.3	<i>Redirect Servers</i>	25
6.9	CANCELING A REQUEST.....	26
6.10	REGISTRATIONS.....	26
6.11	QUERYING FOR CAPABILITIES	26
6.12	DIALOGS.....	26
6.13	INITIATING A SESSION	26
6.14	MODIFYING AN EXISTING SESSION.....	26
6.15	TERMINATING A SESSION	26
6.16	PROXY BEHAVIOR	26
6.17	TRANSACTIONS	26
6.18	TRANSPORT	27
6.19	COMMON MESSAGE COMPONENTS.....	27
6.19.1	<i>SIP URI Component</i>	27
6.20	HEADER FIELDS.....	27
6.20.1	<i>Accept</i>	28
6.20.2	<i>Accept-Encoding</i>	28

6.20.3	<i>Accept-Language</i>	28
6.20.4	<i>Alert-Info</i>	28
6.20.5	<i>Allow</i>	28
6.20.6	<i>Authentication-Info</i>	28
6.20.7	<i>Authorization</i>	28
6.20.8	<i>Call-ID</i>	28
6.20.9	<i>Call-Info</i>	28
6.20.10	<i>Contact</i>	29
6.20.11	<i>Content-Disposition</i>	29
6.20.12	<i>Content-Encoding</i>	29
6.20.13	<i>Content-Language</i>	29
6.20.14	<i>Content-Length</i>	29
6.20.15	<i>Content-Type</i>	29
6.20.16	<i>CSeq</i>	29
6.20.17	<i>Date</i>	29
6.20.18	<i>Error-Info</i>	30
6.20.19	<i>Expires</i>	30
6.20.20	<i>From</i>	30
6.20.21	<i>In-Reply-To</i>	30
6.20.22	<i>Max-Forwards</i>	30
6.20.23	<i>Min-Expires</i>	30
6.20.24	<i>MIME-Version</i>	30
6.20.25	<i>Organization</i>	30
6.20.26	<i>Priority</i>	30
6.20.27	<i>Proxy-Authenticate</i>	31
6.20.28	<i>Proxy-Authorization</i>	31
6.20.29	<i>Proxy-Require</i>	31
6.20.30	<i>Record-Route</i>	31
6.20.31	<i>Reply-To</i>	31
6.20.32	<i>Require</i>	31
6.20.33	<i>Retry-After</i>	31
6.20.34	<i>Route</i>	31
6.20.35	<i>Server</i>	31
6.20.36	<i>FSubject</i>	31
6.20.37	<i>Supported</i>	31
6.20.38	<i>Timestamp</i>	32
6.20.39	<i>To</i>	32
6.20.40	<i>Unsupported</i>	32
6.20.41	<i>User-Agent</i>	32
6.20.42	<i>Via</i>	32
6.20.43	<i>Warning</i>	33
6.20.44	<i>WWW-Authenticate</i>	33
6.21	RESPONSE CODES.....	33
6.22	USAGE OF HTTP AUTHENTICATION.....	33
6.23	S/MIME.....	33
6.24	EXAMPLES.....	33
6.25	AUGMENTED BNF FOR THE SIP PROTOCOL.....	33
6.26	SECURITY CONSIDERATIONS: THREAT MODEL AND SECURITY USAGE RECOMMENDATIONS.....	33
6.27	TABLE OF TIMER VALUES.....	33
7	SIP EXTENSIONS	34
7.1	URIS FOR TELEPHONE CALLS.....	35
7.1.1	<i>Routing Number, Number Portability, Carrier Identification Code, and Dial Around Indication Number</i> 35	
7.1.2	<i>Procedures at an Originating CMS</i>	36
7.1.3	<i>Procedures at a Terminating CMS</i>	36

7.1.4	<i>Procedures at Proxy</i>	36
7.2	RELIABILITY OF PROVISIONAL RESPONSES	36
7.3	SIP UPDATE METHOD	36
7.4	INTEGRATION OF RESOURCE MANAGEMENT AND SIP	36
7.4.1	<i>Procedures at an Originating CMS</i>	37
7.4.2	<i>Procedures at a Terminating CMS</i>	37
7.5	SIP-SPECIFIC EVENT NOTIFICATION	38
7.6	THE REFER METHOD	38
7.6.1	<i>Procedures at an Originating CMS</i>	38
7.6.2	<i>Procedures at a Terminating CMS</i>	38
7.7	SIP PROXY TO PROXY EXTENSIONS FOR SUPPORTING DCS	39
7.7.1	<i>P-DCS-Trace-Party-ID</i>	39
7.7.2	<i>P-DCS-LAES and P-DCS-REDIRECT</i>	39
7.7.3	<i>P-DCS-Billing-Info</i>	44
7.7.4	<i>P-DCS Option Tag</i>	46
7.8	THE SIP "REPLACES" HEADER	46
7.9	PRIVATE EXTENSIONS TO THE SIP PROTOCOL FOR ASSERTED IDENTITY WITHIN TRUSTED NETWORKS	46
7.10	A MESSAGE SUMMARY AND MESSAGE WAITING INDICATION EVENT PACKAGE FOR THE SESSION INITIATION PROTOCOL (SIP)	47
7.11	GLOBALLY ROUTABLE USER AGENT URI (GRUU)	47
7.12	THE EARLY SESSION DISPOSITION TYPE FOR SIP	48
7.13	AN EXTENSION TO THE SESSION INITIATION PROTOCOL (SIP) FOR REQUEST HISTORY INFORMATION	48
7.14	REQUEST AUTHORIZATION THROUGH DIALOG IDENTIFICATION IN THE SESSION INITIATION PROTOCOL (SIP)	48
7.15	THE SESSION INITIATION PROTOCOL (SIP) JOIN HEADER	48
7.16	SUBSCRIBE TO DIALOG EVENT PACKAGE	48
8	CMS-CMS SIGNALING	49
8.1	CMS INTERFACES	49
8.1.1	<i>Overview of CMS Behavior</i>	51
8.1.2	<i>Overview of Tandem Proxy</i>	56
8.2	CMS RETRANSMISSION, RELIABILITY, AND RECOVERY STRATEGIES	56
8.3	CMS TO CMS ROUTING	56
8.3.1	<i>Forming a SIP-URI from a tel-URI</i>	57
8.3.2	<i>Routing a SIP(s) URI at Tandem CMSs</i>	57
8.3.3	<i>Routing based on tel-URI</i>	58
8.4	CMS PROCEDURES	58
8.4.1	<i>CMS Messages and Procedures for Basic Call Setup</i>	58
8.4.2	<i>Emergency Call Procedures</i>	90
8.4.3	<i>CMS Procedures for REFER</i>	97
8.4.4	<i>CMS handling of Mid-Call Changes</i>	102
8.4.5	<i>CMS handling of Call Teardown</i>	110
8.4.6	<i>Sample Implementation of Call Transfer</i>	111
8.4.7	<i>Sample Implementation of Ad-hoc Conference</i>	117
8.4.8	<i>Automatic Recall and Callback</i>	117
8.4.9	<i>Message Waiting Indicator</i>	122
8.4.10	<i>SDP Interworking</i>	124
8.4.11	<i>MGC Caller ID Procedures</i>	128
8.4.12	<i>Procedures for Request History Information</i>	130
8.4.13	<i>Operator Services</i>	136
8.4.14	<i>Signaling Dialed Non-Geographic Numbers</i>	138
9	APPLICATION LAYER ANONYMIZER	139
9.1	SIGNALING CONTENT PRIVACY	140
9.2	IP ADDRESS PRIVACY	140

APPENDIX A TIMER SUMMARY.....143
APPENDIX B CMSS MESSAGE AND HEADER OVERVIEW.....144

LIST OF FIGURES

FIGURE 1. SYSTEM ARCHITECTURE – REALM..... 14
 FIGURE 2. TRUSTED DOMAIN OF IPCABLECOM SERVICE PROVIDER 16
 FIGURE 3. CMS SIGNALING MODEL..... 17
 FIGURE 4. CMS – CMS SIGNALING BASIC CALL FLOW 20
 FIGURE 5. CMS TO MGC SIGNALING..... 22
 FIGURE 6. CMS TO CMS SIGNALING 50
 FIGURE 7. OVERVIEW OF INTERDOMAIN TELEPHONY CALL FLOW..... 51
 FIGURE 8. CALL FORWARDING SUPPORT..... 54
 FIGURE 9. REFER SUPPORT 55
 FIGURE 10. CMS MESSAGES FOR BASIC CALL SETUP..... 59
 FIGURE 11. EMERGENCY CALL; NETWORK HOLD DISCONNECT PROCEDURES 92
 FIGURE 12. EMERGENCY CALL; NETWORK HOLD RESUME PROCEDURES..... 92
 FIGURE 13. EMERGENCY CALL; PSAP OPERATOR RINGBACK WHILE ON HOLD 94
 FIGURE 14. EMERGENCY CALL; PSAP OPERATOR CALLBACK..... 95
 FIGURE 15. END OF TRANSFERRED CALL 112
 FIGURE 16. FAILURE CA– F1 – NO FREE CONFERENCE CIRCUITS 112
 FIGURE 17. ESTABLISHING THE LEG FROM BRIDGE SERVER TO PARTY C..... 113
 FIGURE 18. FAILURE CA– F2 – PARTY C BUSY 114
 FIGURE 19. ON-HOOK INITIATES TRANSFER ACTION 115
 FIGURE 20. RELOCATION OF PARTY B TO BRIDGE..... 116
 FIGURE 21. TRANSFER COMPLETED, CMSI ENDS INVOLVEMENT IN CALL 117
 FIGURE 22. END OF TRANSFERRED CALL 117
 FIGURE 23. MULTIPLE FORWARDING SCENARIO 133
 FIGURE 24. APPLICATION LAYER ANONYMIZER..... 139
 FIGURE 25. ANONYMIZER FUNCTIONS..... 140
 FIGURE 26. PRIVACY ISSUES 141

LIST OF TABLES

TABLE 1 - EGRESS PSTN GATEWAY ENCODING REQUIREMENTS..... 129
 TABLE 2 - INGRESS PSTN GATEWAY ENCODING REQUIREMENTS 130
 TABLE 3 - PARAMETERS AND HEADER FIELDS THAT ARE MODIFIED IN A CMSS COMPLIANT IMPLEMENTATION..... 133

1 INTRODUCTION

1.1 Scope

This specification describes the IPCablecom Call Management Server (CMS) to CMS Signaling protocol intended for use by a CMS to communicate with another CMS in order to support packet-based voice and other real-time multimedia applications. The protocol exchanges between a CMS and a Media Gateway Controller (MGC) are identical to those between CMSs, and so for purposes of this specification the MGC is considered identical to a CMS. CMSs currently support multimedia endpoints (within the IPCablecom infrastructure) that use the Network-based Call Signaling [24] (NCS) protocol and the PSTN Gateway Call Signaling Protocol [25] (TGCP) for communicating signaling information between the endpoint and the CMS. In the future, other protocols may be supported as well, and the CMS to CMS protocol is intended to be sufficiently general to accommodate such protocols without change.

The CMS to CMS protocol uses the Session Initiation Protocol 2.0 (SIP) specification with extensions and usage rules that support commonly available local and CLASSSM services. This protocol is referred to as the Call Management Server Signaling (CMSS) protocol.

The CMSS protocol takes into account the need to manage access to network resources and account for resource usage. The usage rules defined in this specification specifically address the coordination between CMS Signaling and IPCablecom Dynamic Quality of Service (QoS) mechanisms for managing resources over the cable access network. In addition, this specification defines the protocols and messages needed between Call Management Servers for supporting these services.

This document specifies the protocols and procedures to use between CMSs belonging to a single service provider as well as between CMSs that belong to different service providers. In the case that the CMSs are owned by multiple service providers, it is assumed that the service providers have a mutual trust relationship.

Other IPCablecom documents describe interfaces between other system elements. These documents cover areas such as: Event Message recording for billing and other back office functions [23]; Dynamic Quality of Service [21]; Operations and Provisioning [60]; Electronic Surveillance [22]; and Security [26]. These other specifications indirectly place requirements on the signaling protocol to ensure that it transports the correct data needed to implement a complete system. This document includes syntax and protocols for implementing these requirements. Currently, the document does not address interworking with non-IPCablecom-compliant devices.

From time to time this document refers to the voice communications capabilities of an IPCablecom network in terms of "IP Telephony." The legal/regulatory classification of IP-based voice communications provided over cable networks and otherwise, and the legal/regulatory obligations, if any, borne by providers of such voice communications, are not yet fully defined by appropriate legal and regulatory authorities. Nothing in this document is addressed to, or intended to affect, those issues. In particular, while this document uses standard terms such as "call," "call signaling," "telephony," etc., it should be recalled that while an IPCablecom network performs activities analogous to these PSTN functions, the manner by which it does so differs considerably from the manner in which they are performed in the PSTN by telecommunications carriers, and that these differences may be significant for legal/regulatory purposes. Moreover, while reference is made here to "IP Telephony," it should be recognized that this term embraces a number of different technologies and network architecture, each with different potential associated legal/regulatory obligations. No particular legal/regulatory consequences are assumed or implied by the use of this term.